

## **Standard Equipment**

- \*7000 lb Axles
- \* Torsion or Slipper Spring Suspension
- \* Heavy Duty Hanger Group on Spring Suspension
- \* Rubber Bushed Equalizers
- \* Rubber Bushed Large Eye Leaf Spring on Spring Suspension
- \* 8 Bolt Hubs
- \* Grease Bearings
- \* 12x2 Electric Brakes
- \* 16 x 6 Silver Modified Wheels
- \* ST23580R16 E 10 ply Radial Tires
- \* D.O.T. Reflector Strips
- \* Choice of Tailgate
- \* Uprights are 20" on Centers
- \* Floor Cross Members are 12" on Centers
- \* Dualpin SL Drop Leg Jack
- \* Adjustable Coupler for 2 5/16 Ball
- \* Rumbar Solid Bumper
- \* Heavy Duty Extruded Fenders
- \* Bull Nose Front
- \* One Piece Roof Sheet .040 Alum.
- \* Side Entrance Door
- \* Neck Gate
- \* Standard Center Gates
- \* Interior Lights with On/Off Switch
- \* All Aluminum Neck Beams
- \* LED Clearance & Dual Tail Lights
- \* Spare Wheel & Tire Bracket
- \* Step Rail
- \* Neoprene Cold Weather Cord
- \* 7-way RV Electrical End